


RoHS

## SPE-W



Material/Finish



- \*1: This is the value for the plastic material. The maximum operating temperature of the product changes with performance conditions such as tightening torque.
- Part number specification

## SPE-M5-N



- PEEK is a thermoplastic super-engineering plastic with excellent physical and chemical properties.
- These screws have excellent chemical resistance.
   They are mostly unaffected by chemicals excluding concentrate sulfuric acid, concentrate nitric acid, and concentrate hydrofluoric acid.
- These screws have excellent heat resistance, water resistance, and high heat resistance strength.
- These screws have excellent abrasion, shock, and fatigue resistance.
- They have high incombustibility that meets V-0 of UL 94.
- The properties and precautions of plastic screws
   → P.xxxx
- Application

FPD production equipment, semiconductor devices, printed circuit board etching devices, metallic surface treatment equipment and facilities, chemical plants, transformers, electrical and electronic equipment, hot water pumps, and chemical pumps

SPE-N Hex Nuts
Unit:mm

Part Number 1	M (Coarse)		В	т	Mass (g)	Qty
	Nominal of Thread	Pitch	J	•	1VIG33 (g)	per pack
SPE-M2-N	M2	0.4	4	1.6	0.02	20
SPE-M2.6-N	M2.6	0.45	5	2	0.038	20
SPE-M3-N	M3	0.5	5.5	2.4	0.057	20
SPE-M4-N	M4	0.7	7	3.2	0.13	20
SPE-M5-N	M5	0.8	8	4	0.2	20
SPE-M6-N	M6	1	10	5	0.4	10
SPE-M8-N	M8	1.25	13	6.5	0.91	5
SPE-M10-N	M10	1.5	17	8	1.9	5

• When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

SPE-W Washers Unit:mm Qty Part Number 1 d D t Nominal Mass (g) per pack SPE-2-W 2.1 0.5 2 0.0059 20 SPE-2.6-W 2.7 6 0.5 0.015 2.6 20 SPE-3-W 7 0.5 0.02 20 3.2 3 SPE-4-W 4.3 9 0.8 4 0.051 20 SPE-5-W 5.3 10 0.073 20 SPE-6-W 6.4 12.5 1.6 6 0.19 10 SPE-8-W 8 4 17 1.6 8 0.36 5 10.5 21 2 10 0.68 5 SPE-10-W

• When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.