
KNMS-BK Knurled Knobs (Stainless Steel Black)

SUS Stainless steel





|||#||

- Stainless steel black is surface treatment with passive film on the stainless steel surface grown 200 times more than normally to produce deep black. After the treatment, corrosion resistance and weather resistance is significantly improved.
- No impurities are contained in the film itself and only a trace amount of outgas exists in a vacuum environment.
- Spectral reflectivity of 1.5% or below. For applications such as optical equipment that requires antireflection. → P.xxxx
- Deep black. For decorated surfaces of equipment / device.

 Material/Finish 	🗘 Rohs
	KNMS-BK
Main body	SUS303 Stainless steel black

Dimensions								
D 💶	M (Coarse)			_		a		
	Nominal of Thread 4 2	Pitch	п	5	A	u	Mass (g)	
16	M4	0.7	9.5	6	3.5	8	9 - 10	
20	M5	0.8	11.5	7.5	4	10	15 - 16	
24	M6	1	15	10	5	12	28 - 32	
	D 1 6 20	M (Coarse) Nominal of Thread 16M420M5	M (Coarse) Nominal of Thread Pitch 16 M4 0.7 20 M5 0.8	M (Coarse) Pitch Nominal of Thread Pitch 16 M4 0.7 9.5 20 M5 0.8 11.5	M (Coarse) Pitch H A 16 M4 0.7 9.5 6 20 M5 0.8 11.5 7.5	M (Coarse) Pitch H s A 16 M4 0.7 9.5 6 3.5 20 M5 0.8 11.5 7.5 4	M (Coarse) Pitch H s A A 16 M4 0.7 9.5 6 3.5 8 20 M5 0.8 11.5 7.5 4 10	

Part Number	Lm (mm) 📢							
	6	10	16	20	25	30		
KNMS-16-M4-BK	•	•	•					
KNMS-20-M5-BK		•	•	•				
KNMS-24-M6-BK		•	•	•	•	•		

• Part number specification

KNMS	- 24 -	- M6	- 20 -	BK	
Product code	-	1	▲ 3	Stainless Steel Black	
For 🕕 scr	ew lengt	th Lm, se	elect from	n the sizes marked with ●	in
the table.					