




# SPVC-H Plastic Screw - Hex Head Screws - H - PVC

WEB Selection Tool

WEB CAD Download

Chemical-proof



## ● Material/Finish

RoHS2 Compliant

	SPVC-H
Main body	H-PVC (Hard Polyvinyl Chloride)
Heat Resistance Temperature*1	35°C

\*1: This is the value for the plastic material. The maximum operating temperature of the product changes with performance conditions such as tightening torque.

## ● Notice on Product Discontinuation and Launch of Successor Products

H-PVC plastic screws will be discontinued as of the last order on Monday, January 24, 2022.

With some exceptions, the successor products (new products) will be released on Tuesday, January 25, 2022.

For details, refer to

[https://www.nbk1560.com/news/2021/20210512\\_H-PVC\\_SPVC/](https://www.nbk1560.com/news/2021/20210512_H-PVC_SPVC/).

● These products have excellent chemical resistance against strong acids and organic solvents as well as halogen compounds such as hydrogen sulfide and bromine.

● They can be used in atmospheres in which metal and PVC (polyvinyl chloride) cannot be used.

● Max. Operating Temperature\*1 (min./max.):  
-10/35 deg C

● Two colors, ivory and gray, are available.

**IV** ——— Ivory

**GR** ——— Gray

● The properties and precautions of plastic screws  
→ P.xxxx

## ● Application

FPD production equipment, semiconductor devices, printed circuit board etching devices, metallic surface treatment equipment and facilities, and chemical plants

Unit : mm

Part Number	M (Coarse)		L										B	L1	Tension*1 Rupture Load (N)	Mass (g)
	Nominal of Thread	Pitch														
<b>SPVC-M4-H</b>	M4	0.7	10	12	16	20	25	30	35				7	2.8	200	0.3 -0.65
<b>SPVC-M5-H</b>	M5	0.8	10	12	16	20	25	30	35	40			8	3.5	400	0.48 -1.1
<b>SPVC-M6-H</b>	M6	1	10	12	16	20	25	30	35	40	50	10	4	670	0.78 -2	

\*1: Values in chart are for reference only. They are not guaranteed values.

Part Number	Qty per pack
<b>SPVC-M4-H</b>	1
<b>SPVC-M5-H</b>	1
<b>SPVC-M6-H</b>	1

## ● Part number specification

**SPVC-M5-30-H-IV**

Product Code **1** **2** Product Code **3**

Individual Sales → P.xxxxx	Cleanroom Wash & Packaging → P.xxxxx	Screw Length Adjustment → P.xxxxx	Vibration Resistant → P.xxxxx	Modification process for captive use → P.xxxxx
1 unit in 1 bag	Available / Add'l charge	Available / Add'l charge	Not Available	Please feel free to contact us