



- With a pull mounted on it, the pull mounting surface is beautifully decorated while falling of screws within the enclosure is prevented.
- No additional modification of cover or door is required to mount the pull.
- Use it in combination with a captive screw (-).
- For applications such as food machinery, packing machinery and chemical manufacturing devices that require countermeasures against parts falling.

	LYSC-N
Main body	SUS304 Barrel Polishing

RoHS

Part Number	D	M	d	e	A	T	s	Mass (g)
LYSC-12-N	12	M5	4.2	1.2	8.3	2.5	1	1.4
LYSC-16A-N	16	M5	4.2	1.5	10.3	3	1.5	3.1

Unit : mm

Related Products

The captive washer for pulls with a captive screw supplied LYSC-N-SSC is available.



Part number specification

LYSC-12-N

1

- Applicable Captive Screws
Use the captive washer for pull LYSC-N in combination with a compatible captive screw.

Part Number	Applicable Captive Screws				
	SSC	SSCLS	SSCHS	SSCPS	SSCMS
LYSC-12-N	SSC-M5	SSCLS-M5	SSCHS-M5	SSCPS-M5	SSCMS-M5
LYSC-16A-N	SSC-M5	SSCLS-M5	SSCHS-M5	SSCPS-M5	SSCMS-M5

The captive washer for pull LYSC-N cannot be used in combination with any screw or bolt other than a captive screw.

Applicable Pulls

Part Number	Applicable Pulls				
	UNF	UNFS	UNFA	UGF	TG
LYSC-12-N					TG-108 TG-128
LYSC-16A-N	All Sizes			All Sizes	TG-110 TG-130

- Installation Method
 - ① Let the captive screw through the cover and door and tighten it into the screw hole located in the position eccentric from the center of the captive washer for the pull LYSC-N from the pull mounting surface until the cylindrical part of the captive screw is penetrated Figure 2.
 - ② Move the captive screw to the drilled hole at the center of LYSC-N Figure 3.
 - ③ In the state indicated in Figure 3, tighten the captive screw to mount the pull Figure 4.
 - ④ After mounting, the pull screw hole and captive screw are retained at the center of LYSC-N. At this point, the drilled hole at the center of LYSC-N is smaller than the screw part of the captive screw, so the captive screw never comes out of the drilled hole and falling is prevented.

