




e-nedzi.com



## Application

RoHS2 Compliant

Vacuum devices, vacuum chambers, FPD production equipment, semiconductor devices, and electron microscopes

## Material/Finish

	SVLS
Main Body	SUSXM7 (Equivalent to SUS304)
Strength Class	A2-50

- The ventilation hole easily releases gas trapped in the screw holes of equipment and machines, and supports vacuum drawing of vacuum devices.
- Socket head cap screws have low head heights. These screws are intended for the reduction of the size of machinery and device and applications with limited overhead space.
- Cleanroom wash and cleanroom packing are completed. → P.xxxx

																	Unit: mm
Part Number	M	L <b>42</b>								D1	L1	B*2	t	L2*1	d	Mass (g)	
SVLS-M3	M3	6	8	10	12						5.5	2	2	1.5	Full Thread	1.2	0.53 - 0.78
SVLS-M4	M4	6	8	10	12	16					7	2.8	2.5	2.3	Full Thread	1.5	1.1 - 1.9
SVLS-M5	M5		8	10	12	16	20				8.5	3.5	3	2.7	Full Thread	1.5	1.8 - 3.3
SVLS-M6	M6		8	10	12	16	20				10	4	4	3	Full Thread	2	3.1 - 5.3
SVLS-M8	M8			10	12	16	20	25	30	35	13	5	5	3.8	22(L=35)	2	7.2 - 16
SVLS-M10	M10					16	20	25	30		16	6	6	4.5	Full Thread	3	15 - 22


\*1: If the "L" value is other than the value in parentheses, the screw is full thread.

\*2: The hexagonal width across flats of **SVLS-M10** has been changed from 7 mm to 6 mm.

Part Number	Qty* <sup>1</sup> per pack
SVLS-M3	20
SVLS-M4	20
SVLS-M5	10
SVLS-M6	10
SVLS-M8	10
SVLS-M10	5

\*1: Also sold separately from 1 piece up. → P.xxxx

## Usage example Effective with vacuum devices and vacuum chambers that require the exhaustion of gas



• Part number specification



Order in number of packs. Also sold separately from 1 piece up. → P.xxxx

1 Individual Sales → P.xxxxx 💉 Cleanroom Wash & Packaging → P.xxxx 🞳 in Screw Length Adjustment → P.xxxx 🚅 Vibration Resistant → P.xxxx 📫 Modification process for captive use → P.xxxx Available / Add'l charge | Cleanroom washed and packed | Available / Add'l charge | Not Available Please feel free to contact us