SNZF/SNZFS Cross Recessed Flat Head Machine Screws for Precision Instruments

Miniature Size SUS Stainless steel



- Miniature screws for precision instruments.
- M1.4 - M2.6。
- More compact head than standard flat head machine screws.

Application

Reducing the size of equipment and devices
Compact precision instruments

Material/Finish

RoHS

	SNZF-TBZ	SNZFS
Main Body	SWCH16A Black Trivalent Chromate Treatment	SUSXM7 (Equivalent to SUS304)

Unit : mm

SNZF-TBZ Steel - Black Trivalent Chromate Treatment		SNZFS Stainless steel		Common dimensions											Cross-recessed Socket Number	Qty per Pack
Part Number 1	Mass (g)	Part Number 1	Mass (g)	M (Coarse)		L*1 2							D1	L1		
				Nominal of Thread	Pitch											
SNZF-M1.4-TBZ	0.016 - 0.066	**SNZFS-M1.4**	0.016 - 0.066	M1.4	0.3	2	3	4	5	6	8		2	0.45	0	50
		SNZFS-M1.6	0.033 - 0.11	M1.6	0.35		3	4	5	6	8	10	2.3	0.5	0	50
SNZF-M1.7-TBZ	0.027 - 0.13	**SNZFS-M1.7**	0.04 - 0.13	M1.7	0.35	2	3	4	5	6	8	10	2.5	0.5	0	50
SNZF-M2-TBZ	0.038 - 0.18	**SNZFS-M2**	0.056 - 0.18	M2	0.4	2	3	4	5	6	8	10	3	0.6	0	50
SNZF-M2.6-TBZ	0.1 - 0.27	**SNZFS-M2.6**	0.1 - 0.27	M2.6	0.45		3	4	5	6	8		4	0.8	0	50

*1 : SNZFS-M1.7-2-TBZ SNZFS-M2-2-TBZ are not among the standard products.

- When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

Part number specification

SNZFS-M1.7 - 3
1 2

1 Individual Sales ➡ P.xxxx	Cleanroom Wash & Packaging ➡ P.xxxx	Screw Length Adjustment ➡ P.xxxx	Vibration Resistant ➡ P.xxxx	Modification process for captive use ➡ P.xxxx
Available / Add'l charge	Available / Add'l charge	Not Available	Available / Add'l charge	Not Available