


SPA-MC3 Plastic Cross Recessed Micro Pan Head Machine Screws - RENY - Type 3



- High strength
- Lightweight
- Miniature Size
- High Specific Strength



Material/Finish



SPA-MC3	
Main Body	RENY™*1 (50% Glass Fiber Reinforced Polyamide MXD6) (Ivory)
Heat Resistance Temperature*2	105°C

- *1: RENY™ is a trademark or registered trademark of Mitsubishi Gas Chemical Company, Inc.
- *2: This is the value for the resin material. The operating temperature of the product changes with performance conditions such as tightening torque.

Application

Heat insulation and dew condensation prevention of refrigerating and freezing facilities
 Electrical and electronic equipment / Offshore instruments / Plating facilities

- RENY™ miniature screws for precision instruments (No. 0 Class 3).
- RENY™ is a thermoplastic engineering plastic with excellent tensile and bending strength.
- It is highly fatigue-resistant and has excellent creep and heat insulation properties.
- While it is nearly as strong as metal, its weight is approximately 1/5 of iron.
- For the properties and precautions for use of plastic screws, see "Properties of Plastic Screws."
- Mount and remove with **SKCHB** Dedicated Bits and **SRD** Dedicated Magnetic Screwdriver.

Unit : mm

Part Number	M (Coarse)		L							D1	L1	Bit Part No.	Tensile Breaking Load*1 (N)	Torsional Torque*1 (N·m)	Mass (g)	Qty per Pack	
	Nominal of Thread	Pitch															
SPA-M1.2-MC3	M1.2	0.25	1.5	1.8	2	2.5	3	3.5	4	2	0.7	SKCHB-M1.2	116	0.031	0.038 - 0.04	10	
SPA-M1.2-MC3(100)	M1.2	0.25	1.5	1.8	2	2.5	3	3.5	4	2	0.7	SKCHB-M1.2	116	0.031	0.038 - 0.04	100	
SPA-M1.4-MC3	M1.4	0.3			2	2.5	3	3.5	4	6	2.5	0.8	SKCHB-M1.4	165	0.043	0.048 - 0.05	10
SPA-M1.4-MC3(100)	M1.4	0.3			2	2.5	3	3.5	4	6	2.5	0.8	SKCHB-M1.4	165	0.043	0.048 - 0.05	100
SPA-M1.6-MC3	M1.6	0.35			2	2.5	3	3.5	4	6	2.8	0.8	SKCHB-M1.6	154	0.057	0.078 - 0.08	10
SPA-M1.6-MC3(100)	M1.6	0.35			2	2.5	3	3.5	4	6	2.8	0.8	SKCHB-M1.6	154	0.057	0.078 - 0.08	100

- *1: Values in chart are for reference only. They are not guaranteed values. The recommended tightening torque is 50% of the torsional torque.
- When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

Related Products

Mount and remove with **SKCHB** Dedicated Bits and **SRD** Dedicated Magnetic Screwdriver.
 Dedicated Bits **SKCHB**




Dedicated Magnet Screwdrivers **SRD**



Part Number Specification

SPA-M1.2-2-MC3



Individual Sales Available / Add'l charge	Cleanroom Wash & Packaging Available / Add'l charge	Screw Length Adjustment Not Available	Vibration Resistant Not Available	Modification process for captive use Not Available
--	--	--	--------------------------------------	---